


High pressure cleaner
Electrically operated
High pressure cleaner E 240 Ex

EEx II 2G e T 3 RL 94/9/EG
 EEx II 2G e T 4 RL 94/9/EG

Mobile unit for EX-Zone 1/2
Application

For the removal of persistent dirt on the floor or equipment parts in the chemical-, and petrochemical industry as well as raw material-, and waste handling and any explosion protected areas.

Features / Advantages

- High performance data
- Continuous pressure & mass adjustment at the cleaner
- Cleaning solvent exhaust (optional)
- 3 way ceramic piston pump
- Substantial accessories included in the supply
- easy to handle



Mobile high pressure cleaner with 230 bar working pressure, flow rate 1,380 l/h, driven by rotary current 400 Volt, serially equipped with 10m PANZERJET-high pressure hose (500 bar) with hose swivel, spray pistol, turnable screw fitting, insulating handle, double spray wand with pressure regulation, HIP-nozzle, thermostatic valve, five meter electric cable.

Type	Part-No.
E 240 EX T3	2003815
E 240 EX T4	2003816

Technical specification	
Engine	electric motor
Power	6,8 kW / 16 A
Volts / Phase	400 V / 50 Hz. 3 Ph
Pump speed	1.420 1/min
Flow rate	23 l/min max.
Operating pressure	210 bar max.
Unloading pressure	250 bar max.
Water temperature	60°C - 78°C max.
Weight	ca. 120 kg
Dimensions LxWxH	820x700x800 mm

Supplied with	Part.-No.
Highpressure hose, L= 10 m	2003839
Hose swivel	on request
Spray pistol	on request
Double spray lance, L= 1000mm, SS	2003831
Nozzle protection	on request
HIP nozzle, stainless steel	on request
Electrocable, L= 5 m	on request